

**SPECIFICATION SHEET**

=====

**SMPS based BATTERY CHARGER (Auto Float Boost)**

**MODEL** : BCSA3015A

**INPUT**

- \* I/P : 230V AC, 1-Ph, 40-60Hz
- \* Range : 180-270V AC
- \* Fuse Protection.
- \* I/P MOV
- \* Soft Start
- \* Inrush current : 92A@230V AC

**OUTPUT**

- \* Nominal Battery Voltage : 30V DC
- \* Float Voltage : 33.75V
- \* Boost Voltage : 36V
- \* Top up Voltage : 39V(only for Lead acid battery)
- \* Manual -Voltage adj. : 30-40.5V
- \* Current : 15A (adj.4-15A)
- \* Line Regulation : +/- 0.5%
- \* Load Regulation : +/- 1%
- \* Ripple : +/- 1% (P-P)
- \* Noise : +/- 1%
- \* Protections : a) Over load Protection auto recovery type.  
b) Short circuit Protection auto recovery type.  
c) Over Voltage Protection Latching type.  
d) Reverse Polarity Protection by fuse & MCB.
- \* Current Limit

**ENVIRONMENTAL**

- \* Operating temperature 0 to 50<sup>o</sup> C.
- \* Humidity : < 95% Rh
- \* IP 20 Protection

**GENERAL**

- \* Digital Voltmeter & Current meter shall be provided
- \* Input and output MCB 1P shall be provided
- \* Auto / Manual switch shall be provided
- \* Jumper provided to select the battery type - SMF/ Lead Acid
- \* Isolation : Input to Output - 1.5KV  
Input to Earth - 1.5KV  
Output to Earth- 500V

\* MTBF : 50K Hrs to MIL

**INDICATIONS LED** : a) Float  
b) Boost  
c) Equalizer  
g) Top up

**MECHANICAL**

\* Dimension : approx. 295(W) X 180(D) X 265(H)mm

\* Cooling type : Fan

\* Weight : 5.5 Kgs

**OPTIONAL**

\* Load and Battery Terminal separate.