

**SPECIFICATION SHEET**

=====

**DC DC CONVERTER****MODEL** : DC110-1204A**INPUT**

- \* I/P : 110V DC
- \* Range : 90-270V DC
- \* Fuse Protection
- \* I/P MOV
- \* Soft Start

**OUTPUT**

- \* Nominal Voltage : 12V DC
- \* Voltage Range : 10-15V
- \* Current : 4A
- \* Line Regulation : +/- 1%
- \* Load Regulation : +/- 1%
- \* Ripple : +/- 1% (P-P)
- \* Protections : a) Over load Protection auto recovery type.  
b) Short circuit Protection auto recovery type.  
c) Over voltage Protection Latching type.
- \* Current Limit

**ENVIRONMENTAL**

- \* Operating temperature 0 to 50<sup>0</sup> C.
- \* Humidity : < 95% Rh
- \* Enclosure : IP 20 type

**GENERAL**

- \* Isolation : Input to Output -500V
- \* MTBF : 50K Hrs to MIL

**INDICATIONS LED**

- : a) Input OK
- b) Output OK
- c) Output OVP

**MECHANICAL**

- \* Dimension : approx. 135W X 90D X 50H mm
- \* Cooling type : Natural
- \* Weight : approx. 0.5 Kg

**OPTIONAL**

- \* Redundancy by external diode