

SPECIFICATION SHEET

=====

SWITCH MODE POWER SUPPLY

MODEL : PS1210A

INPUT

* I/P : 230V AC, 1-Ph
* Frequency : 47-63Hz
* Range : 180-270V AC
* Fuse Protection. : Yes
* I/P MOV : Yes
* Soft Start : Yes
* Inrush current : 46A@230V AC
* AC Current : 3.5A@230V AC

OUTPUT

* Nominal Voltage : 12V DC
* Voltage Range : 12-15V
* Rated Current : 10A
* Line Regulation : +/- 1%
* Load Regulation : +/- 1%
* Ripple Max : +/- 1% (P-P)
* Noise Max : +/- 1% (P-P)
* Protections
: a) Overload Protection auto recovery type:102-105%
: b) Short circuit protection auto recovery type:Yes
: c) Over Voltage Protection Latching type:105-110%
* Current Limit. : Yes
* Start up time : <1.5sec
* Hold up time : 10ms@230V AC

ENVIRONMENTAL

* Operating temperature 0 to 50⁰ C.
* Humidity : < 95% Rh
* IP 20 protection

GENERAL

* Isolation : Input to Output - 1.5KV
: Input to Earth - 1.5KV
: Output to Earth- 500V
* MTBF : 50K Hrs to MIL

INDICATIONS LED

- : a) Input OK
- b) Output OK
- c) Output OVP

MECHANICAL

- * Dimension : approx. 195W X 130D X 95H mm
- * Cooling type : Fan cooled
- * Weight : 1.4 Kgs

OPTIONAL

- * Redundancy by external diode.
- * Potential Free Contact - Alarm contact
- * Programmable by external signal - voltage & current
- * Remote ON/OFF
- * With Digital Voltmeter & Currenmeter