

SMPS 110V DC 40A

It is modular system and consists of 4 modules of 110V 10A connected in parallel.

SPECIFICATIONS:-

- * Input : 180-270V AC Single phase 47-63Hz
 - * Output :-
 - Voltage : 110V DC (100-150V)
 - Current : 40A (20-40A)
 - Voltage & Current adjustment by pot
 - * Digital voltmeter & current meter shall be provided to read output Voltage & current
 - * Input MCB at back side
 - * Dimension : approx. 485w x 405d x 510h mm
 - * Net weight : approx. 45 kgs.
-

Specifications of 110V DC 10A (each individual unit) :-

I/P : 180 – 270V AC Single Phase

- * With Built in Power Factor Correction
- * Fuse Protection
- * I/P MOV
- * Soft Start

O/P : 110V DC 10A

- * Voltage : 110V DC
- * Current : 10A
- * Line & Load Regulation : Less Than 1%
- * Ripple : Less Than 1% (P-P)
- * Over Load Protection auto recovery type.
- * Short Circuit Protection auto recovery type.
- * Over Voltage Protection Latching type.
- * Over Temperature Protection auto recovery type.
- * Current Limit
- * Operating Temperature 0 to 50° C.
- * I/O Isolation : 2 KV
- * Alarm Contact - Potential Free Contact for output fail.
- * Fan Cooled
- * Enclosure Type : IP20

LED INDICATIONS OF 110V 10A MODULE_:

- 1) Input OK - Green LED
- 2) Output OK-Green LED
- 3) Input Under or Over Voltage (U/O)-Red LED
- 4) Output Over Voltage (OVP)-Red LED
- 5) Output Over Load (O/L)-Red LED
- 6) Output Over Temp (O/T)-Red LED

OPTIONAL

- * Programmable by external signal of 0-5V / 0-10V - voltage & current
- * Control ON/OFF