

SPECIFICATION SHEET

=====

SWITCH MODE POWER SUPPLY

MODEL : PS0804A

INPUT

- * I/P : 230V AC, 1-Ph
- * Frequency : 47-63Hz
- * Range : 90-270V AC
- * Fuse Protection : Yes
- * I/P MOV : Yes
- * Soft Start : Yes
- * Inrush current : 23A@230V AC
- * AC current : 1.5A@230V AC

OUTPUT

- * Nominal Voltage : 8V DC
- * Voltage Range : 7-9V
- * Rated Current : 4A
- * Line Regulation : +/- 1%
- * Load Regulation : +/- 1%
- * Ripple Max : +/- 1% (P-P)
- * Noise Max : +/- 1% (P-P)
- * Protections
 - : a) Overload Protection auto recovery type:102-105%
 - b) Short circuit protection auto recovery type:Yes
 - c) Over Voltage Protection Latching type:105-110%
- * Current Limit. : Yes
- * Start up time : < 1sec
- * Hold up time : 32ms@230V AC

ENVIRONMENTAL

- * Operating temperature 0 to 50⁰ C.
- * Humidity : < 95% Rh
- * IP 20 Protection

GENERAL

- * Isolation : Input to Output - 1.5KV
Input to Earth - 1.5KV
Output to Earth- 500V
- * MTBF : 50K Hrs to MIL

INDICATIONS LED

- : a) Input OK
- b) Output OK
- c) Output OVP

MECHANICAL

- * Dimension : approx. 135W X 90D X 50H mm
- * Cooling type : Natural
- * Weight : approx. 0.5 Kg

OPTIONAL

- * Redundancy by external diode.